

## LUKOIL VERSO LVX

### High-quality Universal Tractor Transmission Oil (UTTO)

#### Specifications

- Massey Ferguson CMS M1145
- Allison C-4
- Caterpillar TO-2
- VCE WB101
- CNH MAT 3525/3509/3505
- Ford ESN-M2C86-B/ESN-M2C86-C
- FORD NEW HOLLAND FNHA-2-C-200.00/201.00
- KUBOTA UDT
- NH 410B
- ZF TE-ML 03E/05F/17E/21F
- API GL-4
- Massey Ferguson CMS M1135/M1141/M1143
- ZF TE-ML 06K
- CASE MS 1210/1207
- Ford ESN-M2C134-D
- John Deere JDM J20C/D
- Landini MACROS/C
- Valtra G2-08

#### Product description

High-performance Universal Tractor Transmission Oil (UTTO) with reduced viscosity for the lubrication of combined systems of hydraulic-transmissions-wet brakes of agricultural equipment.

#### Application

Recommended for use in transmissions, hydraulic and oil-immersed brakes, other ancillary systems fitted to tractors and agricultural machinery of world leading manufacturers.

#### Benefits

##### WEAR PROTECTION

Superior protection under extreme loads and providing long transmission life

##### SMOOTH OPERATIONS

Provides smooth operation of oil-immersed brakes, low noise and vibration levels

##### OXIDATION RESISTANCE

Excellent thermal-oxidative stability

##### STABLE VISCOSITY

High shear stability of viscosity modifier provides long oil life

The product name in an order: Universal tractor oil LUKOIL VERSO LVX, STO 79345251-022-2009

#### Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Viscosity grade	SAE J300	10W-30
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D7042	9.6
Brookfield viscosity at -35 °C, mPa·s	ASTM D2983	24,238
Viscosity index	ASTM D2270	156
Flash Point, COC, °C	ASTM D92	220
Tribological properties on four-ball machine: -Wear scar diameter, mm	GOST 9490	0.36
Pour Point, °C	GOST 20287 B	-41